

#### Attention:

Smoke detectors help people to notice a fire early. However, they cannot extinguish a fire, nor prevent a fire from starting and it also does not alarm the fire brigade.

If danger due to fire exists, the devices emit a loud alarm tone that makes you aware of the danger. Please be aware that people and animals do not smell the deadly poisonous gas when they are asleep. Taking in as little as 3 to 6 breaths of the gases produced by the fire can already be fatal.

Despite the great care taken during manufacture and maintenance of the smoke alarm, it is still possible that malfunctions can occur.

Safety precautions relating to the handling of fire, burning materials and technical devices must always be complied with.

If you should notice that the device is malfunctioning, please inform our service department immediately.

## What to do in the event of fire?

- Keep calm
- Warn all residents
- Help children, disabled, elderly and sick people
- Close all windows and doors behind you
- Exit the house immediately
- Do not use an elevator/lift
- Alarm the fire brigade

**Emergency services: 112**

© Pyrex GmbH

**WBM.** **pyrexX**<sup>®</sup>



## Smoke alarm operating instructions

**WBM – Wohnungsbaugesellschaft Berlin-Mitte mbH**  
**Dircksenstraße 38, 10178 Berlin**  
**Tel: 030/ 2471 5700**

[info@wbm.de](mailto:info@wbm.de) - [www.wbm.de](http://www.wbm.de)

en

Wir freuen uns, dass nun auch Sie durch unsere Rauchmelder geschützt werden. Um einen störungsfreien Betrieb der Geräte zu ermöglichen, sollten Sie den Inhalt dieser Betriebsanleitung beachten:

- Cigarette smoke does not trigger the alarm as long as the smoke is not blown directly into the smoke alarm.
- If the smoke alarm goes off, please check to see if there really is a fire.
- If there is a fire, please immediately start to comply with the instructions on the reverse side.
- If the operational availability of the device is endangered, a short notification tone is emitted at regular intervals (help signal). This can warn about the battery life or about contamination. **In the event of a signal, please inform WBM.**

#### **Please comply with:**

The following ambient influences listed here could result in the smoke alarm's malfunction alarm being triggered:

- Significant cooking, water and frying vapours
- Large fluctuations in temperature
- Room, air and insect spray
- Pollen, construction, grinding and fine dust

In order to avoid the malfunction alarm being triggered, the smoke detector needs to be protected against such ambient influences. The careful and regular cleaning with a vacuum cleaner can also help. Inform your neighbours about a malfunction alarm so that the fire brigade is not unnecessarily alarmed.

Please always ensure sufficient ventilation when cooking. A malfunction alarm can be stopped by pressing the test/stop button (see figure).

Please absolutely pay attention that the air inlets on the circumferential edge of the smoke detector are never impaired by dust, dirt, paint or sticky-tape etc.

#### **Renovation works:**

Before beginning renovation works, the smoke detector should be removed from the magnetic holder by pulling the device lightly and it be stored in a safe place protected from dirt. Please remember to reattach the smoke detector to the magnetic holder. The location of installation should not be changed.



**Ensuring the operational readiness:** Regularly check the operational readiness of your smoke detector yourself. In order to manually check the device, you should push the test/stop button at least once every three months. The entire lower surface is the test/stop button. By applying pressure to this sensor area, you can furthermore temporarily deactivate an alarm or a notification tone (help signal).

#### **Ensuring the operational readiness:**

Carry out a functionality test on your smoke alarm at least once annually in order to ensure that there are no malfunctions or that there is no total outage of the device. Please check:

- Are there smoke alarms present in all rooms and hallways
- Are all smoke inlets free from dirt?
- For a distance of 50 cm, there may not be any obstructing objects (ventilator, lamps, plants).
- Always press the test button to conduct the self-test in the case of each smoke detector. If the confirmation tone sounds, then the smoke alarm is ready for operation.

Results of the examination and any possible other measures need to be recorded. If one or more of these points is not fulfilled, please